

FINISH LINE

PRODUCTS, INC



Finish Line Finish Coat Drywall Surfer

Finish Line Finish Coat Drywall Surfer is a ready to use sprayable drywall surfer used to produce a level 5 finish on gypsum wallboard. Finish Coat produces a finish that is easier to paint, more resistant to abuse damage than regular joint compound or wallboard. Unlike regular drywall primers Finish Coat conceals most sanding fuzz.

Superior Characteristics

- **Reduces labor:**
Faster than skim coating.
- **Easier to paint**
- **More resistant to abuse damage**
- **Conceals most sanding fuzz**
- **Safety:**
The National Institute for Occupational Safety and Health recommends for consumer safety that eye protection be worn. They also suggest a respirator especially in a dry sanding or extremely dusty environment. Finish Line

recommends wet sanding or sponging finished joints to avoid extreme amounts of dust.

- **Warranty:**
Maximum liability shall be limited to replacement of Finish Line's product.
- **Specifications:**
Finish Line Finish Coat Drywall Surfer is a professional quality ready to use sprayable drywall surfer used to produce a level 5 finish on gypsum wallboard.
- **Superior Standards:**
 - Meets ASTM C840 and GA-214 and OSHA safety requirements.

Advantages:

- Factory pre mixed
- Contractor and job site formulated
- Sandable and patchable
- Superior Application Characteristics
- Resistant to abuse damage
- Conceals most sanding fuzz

Job Requirements and Storage:

- Maintain 50° F working temperature until dry, avoid excessive heat and direct sunlight or freezing conditions.

Coverage:

- Average coverage: 75-100 sq. ft/gal. Coverage will vary depending on methods of application and surface porosity.

Available Packaging:

- 5 gal. pail white or tinted
- 275 gal. tote white or tinted

Application:

- Finish wallboard to a Level 4 finish as described in ASTM C840 and GA-214, fix all paper tears and blisters, keep sanding to a minimum and remove any excesses sanding dust. Sweep floors to prevent dust and debris from being disturbed during the application process. Mask all surfaces that will not be covered.

Apply Finish Coat with an airless spray machine using a .623 tip or larger with a minimum pump capacity of 1.0 gpm. Apply a 14 mil coat for best results. Material pressure should be limited to 3000 psig at the machine. Clean up equipment with warm soapy water and rinse with clean tap water.

Finish Coat may be sanded to remove imperfections, overspray, or to yield a smoother surface.

Precautions:

- Wet sanding is recommended
- Use eye protection and a respirator (OSHA approved) while applying
- Do not ingest
- Keep out of reach of children
- This product is intended for interior use only

Submit Approval:

Contractor: _____

Approved By: _____

Job Name: _____

Location of Job: _____

Date: _____

Signatures: _____

Finish Line Finish Coat Product Data:

- Coverage: Average coverage: 75-100 sq. ft/gal. Coverage will vary depending on methods of application and surface porosity.
- Storage: Protect from freezing or overheating and Finish Line Finish Coat will have a shelf life of up to 1 year, under proper storage conditions.
- Available Packaging:
 - 5 gal. pail white or tinted
 - 275 gal. tote white or tinted



PRODUCTS, INC

Finish Line Products
 747 Tucker Road
 Winder, GA 30680

Office (770)-307-1503
Fax (770)-307-1504