

# FINISH LINE

PRODUCTS, INC



## Finish Line Touch-Up

**Finish Line Touch-Up Joint Compound** is a blue tinted ready to use, non-asbestos, vinyl-formulation for embedding drywall tape reinforcement, metal corner beads and drywall trims over wallboard. Touch-Up Joint Compound may also be used for filling, patching and smoothing and finishing coats.

### Superior Characteristics

- **Fast Drying:**

Allowing quick recoat times.

- **Blue Tinted:**

Allowing for easy follow up.

- **Resists Shrinkage and Cracking:**

Ideal because it resists shrinkage, cracks and has excellent adhesion.

- **Consistent from Batch to Batch:**

Finish Line is extremely consistent. We achieve this through thorough testing to make Finish Line products

the best for our consumers.

- **Safety:**

The National Institute for Occupational Safety and Health recommends for consumer safety that eye protection be worn. They also suggest a respirator especially in a dry sanding or extremely dusty environment. Finish Line recommends wet sanding or sponging finished joints to avoid extreme amounts of dust.

- **Warranty:**

Maximum liability shall be limited to replacement of Finish Line's product.

**Specifications:**

Finish Line Joint Compounds are professional quality factory pre mixed vinyl based compounds. They are designed for embedding drywall tape, finishing wallboard joints, patching, fasteners, corner bead and drywall trims. They also can be used for skim-coating, simple hand textures and patching cracks in plaster walls.

**Standards:**

- Meets ASTM C475-89 (standard specification for joint compound and joint tape for finishing gypsum wallboard) and OSHA safety requirements

**Advantages:**

- Fast drying
- Blue tinted
- Factory pre mixed
- Contractor and job site formulated
- Easy to sand
- Approximately 20% lighter than standard joint compound
- Low shrinkage and crack resistant
- Superior Application Characteristics
- Excellent Adhesion

**Job Requirements and Storage:**

- Maintain 50° F minimum working temperature until dry and stable, avoid excessive heat, direct sunlight or freezing conditions

**Coverage:**

- 3.5 gallons covers at least 500 sq ft depending on job conditions and methods of applications

**Available Packaging:**

- 3.5 gal. pail

**Application:**

- Surface should be dry and clean prior to application, final wallboard finish should meet requirements of the five levels of gypsum board finish approved by the gypsum association

**Precautions:**

- Wet sanding is recommended to avoid creating dust
- Use eye protection and a respirator (OSHA approved) when dry sanding
- Do not ingest
- May contain mica, talc, limestone, perlite, plaster, clay and latex
- Keep out of reach of children

**Submit Approval:**

Contractor: \_\_\_\_\_

Approved By: \_\_\_\_\_

Job Name: \_\_\_\_\_

Location of Job: \_\_\_\_\_

Date: \_\_\_\_\_

Signatures: \_\_\_\_\_

**Finish Line Touch-Up Joint Compound Product Data:**

- Coverage: 120 to 155 lb for every 1200 sq. foot of gypsum board (Depending on conditions of application)
- Storage: Protect from freezing or overheating and Finish Line products will have a shelf life of 1 year, under proper storage conditions.
- Finish Line Touch-Up Joint Compound is available in the 3.5 gallon pail.



PRODUCTS, INC

**Finish Line Products**  
747 Tucker Road  
Winder, GA 30680

**Office (770)-307-1503**  
**Fax (770)-307-1504**